



ANCHOR POINTS

- A = 3/4-10 SOLID THREADED ROD QTY 3
- B = 3/4-10 HOLLOW ROD QTY 2
- C = 3/8" SHIELD ANCHORS ON 3.250 BC

SUGGESTED CONDUIT LOCATION

D1 = THROUGH MAIN CHANNEL END CAP (TYP BOTH SIDES)

CONCRETE PAD NOTE:

POUR PAD 4.000 [101.6mm] - 6.000 [152.4MM] THICK, AND ENSURE IT IS LEVEL ±.125 [3.1mm]

PROPRIETARY AND CONFIDENTIAL
THIS DRAWING IS THE PROPERTY OF CONTROLLED ACCESS, INC., AND CONTAINS PROPRIETARY INFORMATION. IT MAY NOT BE COPIED, REPRODUCED OR TRANSMITTED IN ANY MANNER TO A THIRD PARTY WITHOUT PRIOR WRITTEN PERMISSION OF CONTROLLED ACCESS, INC.

| | | | |
|---|---|--------------|--|
| MATERIAL: N/A | SCALE: 1=16 | APPROVED BY: | DRAWN BY: LC III |
| | DATE: 8/11/16 | MS | REVISED: 12/2018 |
| FINISH: TOL. UNLESS OTHERWISE SPEC. .X ± .1 .XXX ± .015 .XX ± .03 ANGLES .5' | CONTROLLED ACCESS, INC. 1636 West 130th Street Brunswick, Ohio 44212 | | 330-273-6185 FAX 330-273-4468 USA 1-800-942-0829 FAX 1-800-942-0828 |
| | | | T80-S ANCHOR POINTS/CONDUIT |