



ANCHOR POINTS

- A = 3/4-10 SOLID THREADED ROD QTY 8
- B = 3/4-10 HOLLOW ROD QTY 4
- C = $\varnothing\frac{3}{8}$ SHIELD ANCHORS ON 3.250 BC QTY 6

SUGGESTED CONDUIT LOCATION

D1 = THROUGH MAIN CHANNEL END CAP (TYP BOTH SIDES)

CONCRETE PAD NOTE:

POUR PAD 4.000 [101.6mm] - 6.000 [152.4mm] THICK, AND ENSURE IT IS LEVEL ± 125 [3.1mm]

PROPRIETARY AND CONFIDENTIAL
THIS DRAWING IS THE PROPERTY OF CONTROLLED ACCESS, INC., AND CONTAINS PROPRIETARY INFORMATION. IT MAY NOT BE COPIED, REPRODUCED OR TRANSMITTED IN ANY MANNER TO A THIRD PARTY WITHOUT PRIOR WRITTEN PERMISSION OF CONTROLLED ACCESS, INC.

MATERIAL:

N/A

FINISH:

TOL. UNLESS OTHERWISE SPEC.
.X \pm .1 .XXX \pm .015
.XX \pm .03 ANGLES .5'

SCALE: 1=16

DATE: 09/2016

APPROVED BY:

DRAWN BY: LC III

REVISED: 12/2018

CA CONTROLLED ACCESS, INC.
1636 West 130th Street
Brunswick, Ohio 44212

330-273-6185
FAX 330-273-4468
USA 1-800-942-0829
FAX 1-800-942-0828

T80-T ANCHOR POINTS/CONDUIT