





















Controlled Access, Inc.

1515 West 130th Street • P.O. Box 430 • Hinckley, Ohio 44233
Ph: (330) 273-6185 • 800-942-0829 • Fax: (330) 273-4468 • 800-942-0828
Sales@CONTROLLEDACCESS.COM
CA-1000-HG-Manual Control Head

  <p>CA-1227 SHAFT-HG-EBS</p>	 <p>CA-1129 ROTARY SHOCK HOLDER</p>
 <p>BEARING INA #S1212 2 REQUIRED</p>	  <p>1/4" X 2" SPRING PIN</p> <p>★</p>
 <p>CA-1103 TENSION SPRING ★ LH SWING</p>	 <p>CA-1221 3" HUB-EBS</p>
 <p>CA-1104 TENSION SPRING ★ RH SWING</p> <p>\$9.30</p>	 <p>3/4" SAE WASHER 2 REQUIRED</p>
 <p>CA-1193 D STOP WITH 1/4-20 SET SCREW</p>	 <p>CA-216 0 TRANTORQUE</p>
 <p>CA-1288 STOP PIN WITH 5/16-18 SET SCREW</p>	 <p>THRUST BEARING DBB-61004</p>
 <p>CA-1211 ROTARY SHOCK ABSORBER 02605318 M20 RH SWING 02605319 M20 LH SWING</p>	 <p>5/16-18 SS BUTTON HEAD CAP SCREW (3) 3/4" LG. (3) 1/2" LG.</p>
 <p>CA-1208 SHOCK COUPLING WITH 5/16-18 SET SCREW</p>	 <p>COMPLETE CONTROL HEAD SPECIFY RH OR LH SWING</p>

★ RECOMMENDED SPARE PARTS